

LASCO CONE WOOD SPLITTER

Patent and trademark protected

Dimensions

Both small forest managers and enterprise contractors rely on this proven and stable splitting technique. Over 8000 LASCO splitters throughout Europe, Canada and the United States have already established themselves in the market bringing maximum benefit and comfort to the forestry sector.

Roli 4.7/5.2/6.2	
A:	358 mm
B:	326 mm
C:	312 mm
D:	340 mm
E:	847 mm

Roli10.0	
A:	371 mm
B:	325 mm
C:	311 mm
D:	343 mm
E:	972 mm

Roli 10.0 K	
A:	371 mm
B:	325 mm
C:	311 mm
D:	465 mm
E:	1084 mm

M1-4.7/5.2/6.2K, M2-4.7/5.2/6.2k	
A:	445 mm
B:	345 mm
C:	361 mm
D:	489 mm
E:	1075 mm

M2-4.7/5.2/6.2 KS	
A:	445 mm
B:	345 mm
C:	365 mm
D:	644 mm
E:	1147 mm

M2-4.7/5.2/6.2 S, M3-4.7/5.2/6.2	
A:	560 mm
B:	460 mm
C:	465 mm
D:	644 mm
E:	1356 mm

M2-4.7/5.2/6.2 M, M3-4.7/5.2/6.2 M	
A:	575 mm
B:	475 mm
C:	475 mm
D:	489 mm
E:	1282 mm

Extremely robust tapered barrel roller bearings Ensure maximum durability.

Cone tips can be easily replaced.

Model	Engi- ne	Vari- ant	Oil capacity	Typical applica- tion weight	Wood		Weight
					Length	Ø	
1-engined							
Roli	6.2		15 - 80 l/min	1,3 - 5,0 to.	200 cm	70 cm	approx. 90 kg.
	5.2		15 - 80 l/min	1,3 - 5,0 to.	200 cm	70 cm	approx. 90 kg.
	10.0		30 - 150 l/min	2,0 - 8,0 to.	300 cm	90 cm	approx. 120 kg.
	10.0	K	30 - 150 l/min	2,0 - 8,0 to.	300 cm	100 cm	approx. 130 kg.
M1	6.2	K	15 - 80 l/min	2,5 - 7,0 to.	300 cm	90 cm	approx. 135 kg.
	5.2	K	15 - 80 l/min	2,5 - 7,0 to.	300 cm	90 cm	approx. 135 kg.
2-engined							
M2	6.2	K	15 - 50 l/min	3,0 - 8,0 to.	400 cm	90 cm	approx. 135 kg.
	5.2	K	15 - 50 l/min	3,0 - 8,0 to.	400 cm	90 cm	approx. 135 kg.
	6.2	S	50 - 200 l/min	5,0 - 15,0 to.	400 cm	110 cm	approx. 320 kg.
	5.2	S	50 - 200 l/min	5,0 - 15,0 to.	400 cm	110 cm	approx. 320 kg.
3-engined							
M3	6.2	S	150 - 300 l/min	8,0 - 25,0 to.	500 cm	150 cm	approx. 400 kg.
	5.2	S	150 - 300 l/min	8,0 - 25,0 to.	500 cm	150 cm	approx. 400 kg.
4-engined							
M4	6.2	S XL	200 - 400 l/min	15,0 - 35,0 to.	700 cm	200 cm	approx. 600 kg.
	5.2	S XL	200 - 400 l/min	15,0 - 35,0 to.	700 cm	200 cm	approx. 600 kg.

Roli	Cone diameter 21cm, hexagonal rapid-change system
K	Cone diameter 28cm
S	Cone diameter 40cm
XL	Cone diameter 60 cm

Engine	max. working pressure
10.0	170 - 200 bar
6.2	170 - 220 bar
5.2	230 - 270 bar

One Cone Splitter - many options!

With the LASCO Cone Splitters you will not only split wood! Diverse attachments transforms the Cone Splitter quickly into a machine with true multiple benefits - thanks to the quick-change system!



The attachments are designed to get even more out of the cone splitter. For this reason, we have designed a quick-change system for the ROLI series.

To ensure that all LASCO cone splitter models can take advantage of the attachments, an adapter is available for all other versions.



The LASCO stump grinder is designed to break down roots, so forest soil can be prepared again for replanting.

A total of nine hardened blades find place on the accessory. In case of an extreme situation where the blades lose their edge, the blades can simply be reversed.



The LASCO weed brush is a reliable device for removing weeds and wild growth e.g. on cobblestones, footpath edges, or parking areas.

By adjusting the height, the pressure on the ground to be cleaned can be adjusted infinitely. All brushes are replaceable and extremely robust.

